

NSF Certified Watertight Plug Options



NEMA L5-15P
 Factory Installed Suffix: PN1
 For 120V Input
 Venture Order Code:
 PG15490



NEMA L6-15P
 Factory Installed Suffix: PN2
 For 240V Input
 Venture Order Code:
 PG15495



NEMA L7-15P
 Factory Installed Suffix: PN3
 For 277V Input
 Venture Order Code:
 PG15500

NSF Certified Watertight Plug Options Accessories

Order Code	Product Description	Voltage	NEMA Description
PG15490	PLUG, MALE, NSF (PN1)	120V	L5-15P
PG15495	PLUG, MALE, NSF (PN2)	240V	L6-15P
PG15500	PLUG, MALE, NSF (PN3)	277V	L7-15P
PG15505	PLUG, FEMALE, NSF (PN1)	120V	L5-15R
PG15515	PLUG, FEMALE, NSF (PN2)	240V	L6-15R
PG15520	PLUG, FEMALE, NSF (PN3)	277V	L7-15R



Male Plug

Female Plug (Connector)

Specification Notes:

UL Listed to UL498

Certified to CSA C22.2 No. 42

Meets NEMA WD-1, WD-6, and ANSI standards

IP66 Suitability

NSF Certified

Moisture Resistance: UL Listed to 3R, 3RX, 4, 4X, 6, 6P, 12

Flammability: UL94V0 (boxes, covers, and plates); UL94V2 (Plugs, connectors, and interiors); UL94HB (Caps, bushings, and cone seals)

Operating Temperatures: -40°C (without impact) to +60°C continuous

UV Resistance: All exposed materials are UV stabilized

NOTE: Other NSF plugs are available, contact Venture Lighting for details

