LINEAR STRIP LIGHT **LUMINAIRES**



Description

Venture Lighting's LED linear strip light luminaires are an excellent choice for either continuous row or stand-alone applications where a valuebased lighting solution is required. Offered in multiple lengths, lumen packages and with a variety of installation mounting feature, Venture's strip lights can be a primary linear solution. In addition to versatility, all of Venture's strip lights allow the ability to maximize your energy savings.

Catalog Number Туре Date Notes

Performance

- CCT options: 3500K, 4000K, or 5000K
- CRI: 80+
- Efficiency of up to 134 lumens per watt

Construction

- The housing is constructed from cold rolled steel to provide rigidity and
- Each housing is finished with a white polyester powder coat.
- · Fixtures are designed for individual or continuous row mounting.
- Each fixture is supplied with a pair of easy-to-use surface mount clips.

- Semi-diffuse acrylic lens standard
- Lens easily removed to allow access to fixture wiring compartment.

Electrical

- Standard Universal Voltage 120-277V 50/60 Hz
- Standard 0-10V DC dimming (Wattage range: 10% to 100%)
- Optional 10W battery back-up factory installation available
- Operating Temperature Range: -4°F to 122°F (-20°C to 50°C)

Installation

- Fixtures snap into surface mount clips (supplied) for quickly installing onto a ceiling or wall.
- · Fixtures are also capable of being suspended by the clip and hook provided.

Controls

- Standard 0-10V DC dimming (Wattage range: 10% to 100%)
- Factory installed motion sensor options available

Warranty

• 5-year warranty

Compliance

- cULus Listed
- Rated for damp and dry locations











Surface mount brackets, included

Ordering & Model Number Information

Luminaire Length	Luminaire Wattage	Order Product Code Description		Model Number	Replaces Existing Luminaire	
4ft		SM55014	3500K; 120-277V; 5850 lm	SM4-45B84AD	2 x 32W T8 Fluorescent	
	45W	SM59116	4000K; 120-277V; 5900 lm	SM4-45N84AD		
		SM19897	5000K; 120-277V; 5940 lm	SM4-45C84AD		
8ft		SM15401	3500K; 120-277V; 7120 lm	SM3-54B88AD		
	54W	SM51723	SM51723 4000K; 120-277V; 7180 lm SM3-54N88AD		80W T12 Fluorescent	
		SM85903	5000K; 120-277V; 7230 lm	SM3-54C88AD		

Factory installed accessories are available, see page 2.

LINEAR STRIP LIGHT LUMINAIRES

Performance Data


	Lumen			Lumens	Amp. Draw (A)		Rated Life	Full Power	Battery Back-up	Battery Back-up
Wattage	CCT	Output	CRI	Per Watt	120V	277V	Hours	IES Files	Mode Lumens	Mode IES Files
	3500K	5850	_	130				<u>IES File</u>	1830	<u>IES File</u>
45W	4000K	5900	80	131	0.38	0.17	50,000	<u>IES File</u>	1850	<u>IES File</u>
	5000K	5940	-	132				<u>IES File</u>	1860	<u>IES File</u>
	3500K	7120	_	132				<u>IES File</u>	1880	<u>IES File</u>
54W	4000K	7180	80	133	0.45	0.20	50,000	<u>IES File</u>	1900	<u>IES File</u>
	5000K	7230		134				<u>IES File</u>	1910	<u>IES File</u>

Photometrics




Luminious Intensity Distribution Diagram

54W Linear Strip Light



Dimensions



Accessories

□ PH41623 – Motion only control sensor

□ PH77409 - Motion/Photocell/Dim control sensor

□ AC25420 – 3/8" 3-wire 14/3 600V Max. 6ft Flex. Whip

☐ AC13812 — V-hooks (for suspension mount)

☐ AC20156 — V-hooks with 6ft cables (for suspension mount)

☐ AC35187 — Row alignment accessory (for continuous row mounting)

□ LN18733 – Replacement 4ft lens, acrylic

□ LN18734 – Replacement 8ft lens, acrylic

□ KT12139 – 4ft wire guard kit, (2) would be required for 8ft fixtures

Factory installed accessories:

- Add suffix "-S1" for a MOTION ONLY Sensor; Part # PH41623
- Add suffix "-S2" for a MOTION/DIM/PHOTOCELL Sensor; Part # PH77409

Ο,

- Add suffix "-EM" for a 10W battery back-up
- Add suffix "-WP1" for 6ft 3-wire whip on the end of the strip
- Add suffix "-WP2" for 6ft 3-wire whip on the back of the strip

(800) 451-2606

6675 Parkland Blvd., Suite 100 Solon, Ohio 44139 USA Email: Venture_Lighting@VentureLighting.com

VentureLighting.com

