

DLC® Model# PD24-48B-BNR-X00



Description

The Venture Lighting LED panel series of luminaires are low profile, lightweight, and designed for long life and low maintenance. These are designed to quickly and easily upgrade existing fluorescent fixtures. LED color consistency meets a 4-step MacAdam ellipse.

Construction

The high performance LED source is mounted to ensure proper thermal management of the system. The design allows for a cooler running LED chip which leads to longer lifetime, better efficacy, and color consistency.

Optics

The fixtures are designed to have low glare yet utilize high performance materials to maximize efficacy and achieve precise photometric distributions.

Electrical

The power supply has a range of 200-347V, 50/60 Hz. 0-10V DC dimming capability is standard. The fixture is rated for damp and dry locations. Fixtures are IC-rated.

Mounting

The fixture is designed for replacing fluorescent fixtures.

Product Performance

Wattage	48W
Lumens	5170
Correlated Color Temperature (CCT)	3500K
Color Rendering Index (CRI)	80
Life Hours	50000
Operating Temperature Range	-13°F to 113°F (-25°C to 45°C)

Physical Characteristics

Fixture Color	White
Length	47.7"
Width	23.7"
Height	1.9"
Panel Size	2x4
Weight	20.2 lbs

Electrical Characteristics

Amperage Draw (Input Volts/Amps)	347/0.16
----------------------------------	----------

Regulatory Qualifications

cULus Listed
DLC® Qualified - Model# PD24-48B-BNR-X00
IC-rated


Accessories

KT18522 2X4 SURFACE MOUNT KIT, WHITE
KT18916 2x4 DRYWALL MOUNT KIT, WHITE
AC25420 - 3/8" 3-WIRE 14/3 600V MAX 6FT FLEX. WHIP
Add suffix "-WP" to order code for a factory installed fixture with a 6ft whip (Part # AC25420)




Venture 48W LED Panel (2x4), 3500K


Luminous Intensity Distribution Diagram



48W 2x4 LED Panel



Average Illuminance Curve



(800) 451-2606
 Fax: (800) 451-2605
 7905 Cochran Rd, Suite 300
 Glenwillow, Ohio 44139
 E-mail: Venture_Lighting@VentureLighting.com
VentureLighting.com

