



Description

Venture Lighting's LED Retrofit lamps are the ideal upgrade solution to traditional HID lamp technologies. Venture's LED Retrofit lamps are a simple energy saving solution for providing significant maintenance savings. The integrated driver design is an ideal upgrade from traditional technologies.

Features & Benefits

- Replaces MH or HPS up to 175W*
- Replaces CFL up to 85W*
- 5 year warranty
- Universal burn position
- Easy installation
- Reduced maintenance costs
- **Note: It is the customer's responsibility to verify that the lamp compartment meets the minimum required lamp compartment dimension of 8" diameter by 11" long.*

Applications

- Post top
- Wall pack
- Area Lighting
- Flood lighting
- Garage lighting
- General illumination

Notes

- The use of an external surge protection device is recommended.
- Operating temp. range between -40°F and 122°F (-40°C and 50°C).
- Suitable for use in dry and damp environments.
- Suitable for use in portable, surface mounted and ceiling luminaires.
- Suitable for use in open and enclosed luminaires with minimum lamp compartment dimensions of 8 inch diameter x 11 inch deep.
- Do not use where exposed to water or outdoors without an appropriate enclosed luminaire.
- Lamps have clear polycarbonate cover lenses

VL1-OR036-50E39-AE00

Product Performance

| | |
|------------------------------------|--------------------------------|
| Input Power (W) | 36 |
| Bare Lamp Lumens | 4320 |
| DLC Rated Lumens | 3350 |
| Lumens/Watt (Bare Lamp) | 120 |
| Correlated Color Temperature (CCT) | 5000K |
| Color Rendering Index (CRI) | 80 |
| Life Hours | 50000 |
| Minimum Lamp Compartment Size | 8" Dia by 11" long |
| Dimming | No |
| Operating Temperature Range | -40°F to 122°F (-40°C to 50°C) |

Physical Characteristics

| | |
|------------------|-----------------|
| Base Type | Mogul, (E39) |
| Overall Length A | 9.25" (235mm) |
| Diameter B | 3.66" (93mm) |
| Weight | 1.8 lbs (816 g) |

Electrical Characteristics

| | |
|---------------------|----------------------|
| Input Voltage Range | 100V-277V; 50/60Hz |
| Driver | Internal within lamp |
| Power Factor | >0.90 |
| THD | <20% |

Regulatory Qualifications


- cULus Listed
- cULus Classified – Certified to UL 1598C
- DLC Qualified - Model# VL1-OR036-50E39-AE00

Accessories

- SP12714 – 120-277V Surge Protector



Venture 36W LED Retrofit Lamp



(800) 451-2606
Fax: (800) 451-2605
2451 Enterprise Parkway East
Twinsburg, Ohio 44087 USA
E-mail: venture@adlt.com
VentureLighting.com

