



- Edge-lit, frosted optic with a 120° beam angle; Designed for low glare and maximizes product performance
- Thin profile and easy to handle
- For retrofit or new construction with T-Bar applications
- DesignLights Consortium® (DLC) qualified
- 50,000 hour life
- 5 year warranty
- Rated for damp and dry locations
- IC rated for direct contact with insulation
- 0-10V DC dimming standard to maximize energy savings
- Panels can be mounted in a recessed ceiling (T-grid), surface mounted (optional), or suspended (optional)



Venture Lighting's LED Panels are Available in 2x4, 2x2, and 1x4

LED FLAT PANELS

CCT Selectable LED Panels

Panel Size	Order Code	Product Description
2x4	PN41751	48W 2X4 Panel; CCT: 3500K, 4000K, 5000K; 100-277V

Single CCT LED Panels

Panel Size	Order Code	Product Description
1x4	PN17467	36W 1X4 LED Panel; 3500K; 100-277V; White; 3900 lm
	PN21852	36W 1X4 LED Panel; 3500K; 100-277V; White; 3350 lm
	PN14614	36W 1X4 LED Panel; 4000K; 100-277V; White; 3950 lm
	PN51267	36W 1X4 LED Panel; 5000K; 100-277V; White; 4040 lm
	PN15025	36W 1X4 LED Panel; 3500K; 200-347V; White; 3800 lm
	PN52157	36W 1X4 LED Panel; 4000K; 200-347V; White; 3870 lm
2x2	PN26744	40W 2X2 LED Panel; 4000K; 100-277V; White; 4600 lm
	PN54241	40W 2X2 LED Panel; 4000K; 200-347V; White; 4460 lm
	PN21336	40W 2X2 LED Panel; 5000K; 100-277V; White; 4180 lm
	PN41258	40W 2X2 LED Panel; 5000K; 100-277V; White; 4735 lm
	PN28633	40W 2X2 LED Panel; 4000K; 120-277V; White; 4030 lm
	PN45124	48W 2X4 LED Panel; 5000K; 100-277V; White; 5520 lm
2x4	PN41312	48W 2X4 LED Panel; 3500K; 200-347V; White; 5170 lm
	PN58134	48W 2X4 LED Panel; 4000K; 200-347V; White; 5300 lm



**CONTACT YOUR VENTURE LIGHTING
INSIDE ACCOUNT REPRESENTATIVE TODAY!**

(800) 451-2606 VentureLighting.com