



Twist lock photocell sensor

Order Code: PH87145

Product Information

Rated Voltage	347V AC
Max. Load	10VA
Connection Type	Conforms to ANSI C136.10
Housing	UV stabilized polypropylene
Photocell	Broad surface sensing element
Turn-on	1 to 3 foot-candles
Switch Type	Single-pole, single-throw
Dimensions	3.3" Dia. x 2.36" Height

cULus Listed

The photocell cap is gasketed and contains a built-in time delay which prevents false cycling caused by lightning flashes or stray headlights.

Twist lock photocell sensor

Order Code: PH12415

Product Information

Rated Voltage	105-305V AC
Max. Load	10VA
Connection Type	Conforms to ANSI C136.10
Housing	UV stabilized polypropylene
Photocell	Broad surface sensing element
Turn-on	1 to 3 foot-candles
Switch Type	Single-pole, single-throw
Dimensions	3.3" Dia. x 2.36" Height

cULus Listed

The photocell cap is gasketed and contains a built-in time delay which prevents false cycling caused by lightning flashes or stray headlights.

Twist lock photocell sensor

Order Code: PH81156

Product Information

Rated Voltage	480V AC
Max. Load	10VA
Connection Type	Conforms to ANSI C136.10
Housing	UV stabilized polypropylene
Photocell	Broad surface sensing element
Turn-on	1 to 3 foot-candles
Switch Type	Single-pole, single-throw
Dimensions	3.3" Dia. x 2.36" Height

cULus Listed

The photocell cap is gasketed and contains a built-in time delay which prevents false cycling caused by lightning flashes or stray headlights.



Shorting Cap

Order Code: PH81975

Product Information

Rated Voltage	120-480V
Max. Load	1800VA
Connection Type	Conforms to ANSI C136.10

cULus Listed

The shorting cap is gasketed and contains a shorting connection between the line and load of the receptacle keeping the lights ON as all times when power is supplied.

