

18W LED 6" 5000K Downlight

Order Code: DL38412



Description

Venture Lighting's LED downlight retrofit kits are low profile, durable, and designed for long life and low maintenance. Designed to fit into existing 8" diameter openings, these retrofit kits quickly and easily upgrade metal halide wattages and compact fluorescent wattage with an energy saving LED 40W. These downlights have lower heights compared to our other LED downlights. They are also more efficient and comply with all U.S. and Canadian safety standards.

Optics

Designed to have low glare yet utilize high performance materials to maximize efficacy and achieve precise photometric distributions, these downlights come standard with a 90-degree beam angle.

Electrical

The power supply has a range of 120-277V, 50/60 Hz. The high-performance LEDs are rated up to 54,000 hours at 25°C ambient temperature. 0-10V dimming capability is standard.

Mounting

The kits are NON-IC Rated and designed for replacing most manufacturer's CFL and HID fixtures.

Warranty

For warranty information refer to: www.venturelighting.com/resources/warranties

Product Performance	
Wattage	18W
Lumens	1318
Correlated Color Temperature (CCT)	5000K
Color Rendering Index (CRI)	80+
Life Hours	54,000
Beam Angle (°)	90°
Operating Temperature Range	-4°F to 113°F (-20°C to 45°C)

Physical Characteristics	
Diameter	7.48"
Trim Color	White
Height	5.68"
Weight	1.85 lbs

Electrical Characteristics	
Amperage Draw (Input Volts/Amps)	120/0.15 208/0.09 240/0.08 277/0.07

Regulatory Qualifications
cULus Classified
Energy Star Model No. DLB-1801C-WH
Rated for dry and damp locations

Α	(Дς	CL	۱۲ı	Д

KT86415 – New construction kit – 6"

BB24622 – Battery back-up (Lumens: 1402) (0-50°C)†

Revision: 04, 26-Aug 2022

Notes

† Operating temperature range for battery back-up









Venture 18W LED 6" 5000K Downlight

Dimensions





(800) 451-2606

6675 Parkland Blvd., Suite 100 Solon, Ohio 44139 USA Email: Venture_Lighting@VentureLighting.com



