

12W LED Retrofit Lamp

Order Code: LP23242



Description

Venture Lighting's LED Retrofit lamps are the ideal upgrade solution to traditional HID lamp technologies. Venture's LED Retrofit lamps are a simple energy saving solution for providing significant maintenance savings. The integrated driver design is an ideal upgrade from traditional technologies.

Feature & Benefits

- Energy Saving Replacement for MH or HPS
- Up to 5 times longer life and 80% energy savings compared to HID
- 5 year warranty
- Universal burn position
- Easy installation
- Reduced maintenance costs

Applications

- Post top
- Wallpack
- Area lighting
- Flood lighting
- Garage lighting
- General illumination

Notes

- The use of an external surge protection device is recommended
- Operating temp. range between -40°F and 113°F (-40°C and 45°C)
- Suitable for use in open and enclosed luminaires
- Suitable for use in dry and damp environments
- Do not use where exposed to water or outdoors without an appropriate enclosed
- Lamps have clear polycarbonate cover lenses

For warranty information refer to: www.venturelighting.com/resources/warranties

12
1700
140
4000K
80
50000
1.8" x 7.1" x 7.1" (300mm x 180mm x 180mm)
No
-40°F to 113°F (-40°C to 45°C)

Physical Characteristics	
Base Type	Medium (E26)
Overall Length A	4.92" (125mm)
Diameter B	2.36" (60mm)
Weight	0.48 lbs (0.22 kg)

Electrical Characteristics	
Input Voltage Range	100-277V; 50/60Hz
Power Factor	<u>≥</u> 90%
THD	<u>≤</u> 20%

Regu	laton	<i>i</i> 0	ual	ifica	tions
NUSU	ιαισι	I Y	uui	mca	เมษาว

cULus Listed (UL 1993/CSA C22.2 No. 1993)

cULus Classified (UL 1598C/CSA C22.2 No. 250.1)

Accessories


SP12714 120-277V Surge Protector


Revision: 02, 07-Sept 2022





Venture 12W LED Retrofit Lamp





Easy to install - bypass ballast and provide voltage directly to lamp

(800) 451-2606

6675 Parkland Blvd., Suite 100 Solon, Ohio 44139 USA Email: Venture_Lighting@VentureLighting.com



